

Fan and Blower - Capacitor Start, Dripproof Resilient Base (Single & Two-Speed)

Features:

- Ball bearings
- Heavy gauge steel frame and base
- Service Factor, as noted
- Capacitor start / capacitor run as noted
- Thermal protection, as noted
- 48Y and 48YZ Frame have 48/56 Frame mounting holes
- UL Recognized and CSA Certified



MARATHON

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	F.L. AMPS	WEIGHT	"C" DIM.	FOOT NOTES	
1/4	1725	115/230	48	NONE	G1114	5KC35JN7J	✓	5.2/2.6	16	9.57	20	
	1725	115/208-230	48YZ	AUTO	B313	48C17D2042	✓	5.2/2.8-2.6	16	9.95	CF,20,31,52	
	1725	115/208-230	48YZ	NONE	B312	48C17D2041	✓	6.2/2.8-3.1	15	9.72	20,31,52	
	1725	115/230	48	AUTO	G1115	5KC35JN7X	✓	5.2/2.6	16	9.57	20	
1/3	1725	115/208-230	48YZ	NONE	B314	48C17D2043	✓	5.8/3.1-2.9	18	10.22	20,31,52	
	1725	115/208-230	48YZ	AUTO	B315	48C17D2044	✓	5.8/3.1-2.9	17	10.22	20,31,52	
	1725	115/208-230	56	AUTO	C216	5KC36LN1X	✓	6.0/3.2-3.0	18	10.32	20,50	
	1725	115/230	48YZ	AUTO	D119	48C17D2055	✓	5.8/2.9	12	10.22	20,31,52	
	1725	115/230	56	AUTO	G135	56C17D2088	✓	6.4/3.2	18	10.22	20	
	1/2	3450	115/208-230	48	AUTO	C1152	5KC39QN3220X	✓	8.2/3.9-4.1	19	11	19
1725/1140		115	56	AUTO	C419	5KC49PN3027X	✓	8.2/3.9	28	11.38	19	
1725		115/208-230	56	NONE	B1316	5KC49GN0001	✓	8.8/4.2-4.4	21	10.38	19	
1725		115/208-230	56	AUTO	C1153	5KC49GN0022X	✓	8.6/4.1-4.3	21	10.38	19	
1725		115/208-230	56	AUTO	B317	56C17D2072	✓	8.0/4.1-4.0	20	10.32	CF,19,31	
1725		115/208-230	56Y	AUTO	B353	56B17D67	✓	6.2/3-3.1	24	12.92	1,19,55	
1725		115/230	56	AUTO	D111	56C17D2079	✓	7.2/3.6	20	10.72	19	
1725		115/230	56	AUTO	G151	56C17D2025	✓	8.6/4.3	24	11.72	19	
1725		277	56	NONE	B608	56C17D2113	✓	3.6	23	11.72	19	
3/4		3450	115/208-230	56	AUTO	C1155	5KC38NN410X	✓	10.0/4.9-5.0	17	11.32	19
	3450	115/208-230	48	AUTO	C1154	5KC38NN413X	✓	9.8/5.0-4.9	17	11	19	
	1725/1140	115	56	AUTO	B332	56B17D5701	✓	8.9/6.1	40	12.85	1,19,31	
	1725/1140	115	56	NONE	C420	5KCR49PN3011	✓	9.0/6.4	31	11.48	ES,1,19	
	1725/1140	208-230	56	NONE	C486	5KCR49PN3012X	✓	4.3-4.4/3.1-3.2	38	11.48	ES,1,19	
	1725/1140	115	56	AUTO	C474	5KCR49PN3011X	✓	9.0/6.4	31	11.48	ES,1,19	
	1725	115/208-230	56	AUTO	C1156	5KC46LN0149X	✓	13.3/6.5-6.6	27	10.78	19	
	1725	115/208-230	56	AUTO	B319	56C17D2074	✓	10.0/5.2-5.0	23	10.72	CF,19,31	
	1725	115/208-230	56	NONE	CG230	5KC46LN0158	✓	13.2/6.2-6.6	25	10.78	19	
	1725	115/208-230	56	NONE	B318	56C17D2073	✓	10.0/5.2-5.0	24	10.72	CF,19,31	
	1725	115/208-230	56	NONE	G156	56B17D2012	✓	11.0/5.5-5.5	26	11.47	1,19	
	1725	115/208-230	56Z	AUTO	4686	5KC46LN0269X	✓	13.3/6.5-6.6	25	11.15	10,19	
	1725	115/230	56	AUTO	D1113	5KC46LN0158X	✓	13.2/6.6	25	10.78	19	
	1725	277	56	NONE	B609	56B17D2013	✓	4.3	27	11.47	1,19,31	
	1	3450	115/208-230	56	AUTO	C1157	5KC39RN383X	✓	13.4/6.7-6.6	25	11.85	19
		3450	115/208-230	56	AUTO	D118	56C34D2106	✓	12.0/6.2-6.0	25	12.22	18
1725/1140		115	56	AUTO	B335	56B17D5703	✓	11.5/7.0	39	12.85	1,18,31	
1725/1140		115	56	NONE	C475	5KCR49SN3009	✓	10.8/7.4	35	12.01	ES,1,18	
1725/1140		115	56	AUTO	C1478	5KCR49SN3009X	✓	10.8/7.4	30	12.01	ES,1,18	
1725/1140		208-230	56	NONE	C476	5KCR49SN3010	✓	5.3-5.4/3.6-3.7	35	12.01	ES,1,18	
1725/1140		208-230/190-380	56H	AUTO	C1479	5KCR48TN3084X	✓	5.3-5.4/3.6-3.7	36	12.54	ES,1,17	
1725		115/208-230	56	AUTO	C1158	5KC49PN0164X	✓	14.7/7.2-7.4	29	11.38	18	
1725		115/208-230	56Z	AUTO	4688	5KC49NN0061T	✓	14.4/7.2-7.4	28	11.75	10,18	
1725		115/208-230	56H	NONE	C235	5KC49PN0155	✓	13.6/6.7-6.8	31	11.38	18	
1725		277	56	NONE	B337	56C17D5348	✓	5.6	29	11.85	19,32	
1 1/2		3450	115/208-230	56H	AUTO	D115	56B34D2027	✓	13.4/7.4-6.7	28	11.72	1,18
	1725	115/208-230	145T	NONE	I146	145TCDR5331	✓	18.0/9.3-9.0	42	13.22	18,32	
	1725	115/208-230	56H	NONE	B336	56C17D5347	✓	18.0/9.3-9.0	39	12.85	5,18,32	
	1725	115/208-230	56H	AUTO	C1160	5KCR49SN0150X	✓	16.4/8.4-8.2	35	11.91	ES,1,18	
	1725	277	56H	NONE	B338	56C17D5349	✓	7.5	41	12.85	5,18,32	
2	3450	115/208-230	56H	AUTO	C1161	5KCR49RN2148T	✓	19.6/10.4-9.8	33	11.91	ES,1,110	
	1725	115/208-230	56H	AUTO	B352	56B17D5331	✓	21/11.3-10.5	50	13.85	1,5,32	
	1725	115/208-230	145T	NONE	I147	145TBDR5345	✓	21/11.3-10.5	49	14.22	1,18	