



# Submittal Data

MODEL  
REG-253R

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

### PERFORMANCE DATA

Power supply 1Ph,230/208V-,60Hz

#### Cooling

Capacity	Btu/h	25000/24700
Input	W	2660/2628
Rated current	A	11.3/12.4
Max. Current	A	16.80
CEER	Btu/w	9.4
EER		9.4

#### Heating

Capacity	Btu/h	16000/13000
RATED Input(Heater)	W	4800/ 3925
Rated current	A	22.5 / 20.0

#### Compressor Electrical

Model	PA236G2C-3MTL	
Type	Rotary	
Brand	GMCC	
Capacity	Btu/h	28183
Input	W	1885
Rated current(RLA)	A	8.4
Refrigerant type	oz	R410A/34.22

#### Air flow & Noise level

Indoor air flow	CFM	523/485/445
Indoor noise level	dB(A)	63.2/60.5/58.2
Outdoor air flow	CFM	823/755/683
Outdoor noise level	dB(A)	68.2/65.6/63.4
Window Opening	Min/Max Width	31/42
	Min Height	19.5

#### Accessories

AS080	Window AC Support Bracket
NTN-2	Window AC Support Bracket



#### Fan Motor

Model	YKSS-150-6-7L(YSK150-6BS(B)	
Input	W	275
Speed	RPM	1120/1030/930

#### Dimensional Data

Dimension(W*D*H)	inch	26.5x26.5x18.6
Packing (W*D*H)	inch	29.5x31.3x20.5
Net/Gross weight	lbs.	136.5/155.6

#### SYSTEM DATA

Design pressure	PSIG	300/520
Thermostat type		Touchpad/Remote
Application area (Cooling EPA)		1400-1500

#### Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-30P

